

Mercury & Gas in Metal Thermometers (Temperature Gauges)



www.dynamicgauges.com

Typical Applications

These temperature gauges are used in Corrosive Medium & Chemical Environments, for higher temperature measurements.

Standard Features

Nominal Sizes:

63, 100, 115 and 150mm

Scale Ranges:

In Fahrenheit, in Centigrade and Dual Scale
-50°C to 650°C

Accuracy Class:

±1.0% FSD

Stem Dia:

6mm, 8mm, 10mm

Connection:

1/4", 3/8", 1/2" BSP / NPT, Fix / Adjustable

Mounting:

Bottom or Back Mounting

Liquid Filling:

Yes

Weather Protection:

IP 56

Special Versions / Optional / Extras:

- + Surface Mounting,
- + Panel Mounting,
- + Bracket Mounting
- + with Distance Capillary Alarm Contact
- + External Zero Adjustment



Sensor

Mercury / Gas

Pointer:

Zero Adjustment

Wetted Part:

SS 304 / 316

Window:

Toughened/Safety Glass

Case Material:

Stainless Steel 304

Dial:

White Aluminium with Red & Black lettering

* Specifications may be modified without prior notice. Please contact & confirm before placing order

Dynamic Gauges Pvt. Ltd.

Unit No. 3 & 4, Sami Ullah Khan Compound, Wakan Pada, Vasai Phata, Vasai (East), Thane – 401 208. Maharashtra, INDIA
Tel: +91 (0250) - 3057800/1/2 Ext 216 / 217 / 218 (Fax) Mobile: +91 98202 31751 Email: sales@dynamicgauges.com